



KONICA MINOLTA

KONICA MINOLTA FAX
3900

A powerful multifunction fax solution for moving fax information and images more quickly, to more destinations – perfect for mid-sized businesses, branch offices, and departments requiring quick fax communication with clients, suppliers, and co-workers.

16 ppm printing and up to 600 dpi for high-resolution image quality that makes text more legible, fine details and handwritten notations crisper and clearer.

Color scanning support allows you to scan color originals as well as black-and-white originals; TWAIN scanning lets you scan documents directly to your PC.

Network scan/Internet fax functions let you convert paper documents to electronic files for archiving and distribution; Scan-to-Email and Scan-to-FTP lets you store, share, edit and distribute scanned data in TIFF or PDF format.


High-speed Super G3 Fax with built-in modem transmits at up to 33.6 Kbps; ultra-fast scanning in as little as 2.5 seconds per page.

Standard 16 MB memory is upgradeable to 48 MB to store up to 1,024 fax pages for greater productivity.

High-quality copying with Micro-toning for superior image quality, Text Mode for more legible text, Photo Mode for smooth halftone reproduction.

Convenient fax functions include 200 Auto Dialing locations, 64 One-Touch Dialing locations, 274 Broadcast locations, F-Code support, Timer transmission and more.

High paper capacity including 50-sheet Automatic Document Feeder, 200-sheet output tray, 250-sheet paper cassette, and optional 500-sheet second paper cassette unit.



Multifunction Laser Facsimile. A simple, powerful solution for mid-volume and high-volume fax traffic. With network scanning and Internet faxing for electronic archiving, file distribution and sending faxes over the Internet. TWAIN color scanning. And fast, 16ppm print/copy output.

FAX3900



The essentials of imaging



Konica Minolta FAX3900

General Specifications

TYPE:
Desktop facsimile transceiver

COMMUNICATION LINE:
Public switched telephone network (PSTN)

CAPABILITY:
Super G3

DATA COMPRESSION:
MH/MR/MMR/JBIG

SCANNING SYSTEM:
CIS (Contact Image Sensor)

MODEM SPEED:
33.6 Kbps (max)
14,400, 9600, 7200, 4800, 2400
bps (automatic fallback)

FAX TRANSMISSION SPEED:
3 seconds per page*

FAX SCAN SPEED:
2.5 seconds per page

FAX SCAN RESOLUTION:
300 x 300 dpi (ADF)
Standard: 203 x 98 dpi
(Memory TX)
Fine: 203 x 196 dpi
(Memory TX)
Superfine: 203 x 392 dpi
(Memory TX)

SCANNER SCAN SPEED:
Black:
150 x 150 dpi: 3 seconds per page
300 x 300 dpi: 6 seconds per page
600 x 600 dpi: 12 seconds per page
Color:
150 x 150 dpi: 26 seconds per page
300 x 300 dpi: 52 seconds per page
600 x 600 dpi: (not applicable)

PRINT SPEED:
Up to 16 pages per minute

PRINT RESOLUTION:
300 x 300 dpi (standard GDI) or
600 x 600 dpi (standard GDI)

PRINT SIZE:
8-1/2" x 11" (letter)
8-1/2" x 14" (legal)

PAPER SUPPLY:
250-sheet standard paper drawer
(20 lb. bond)
500-sheet second paper cassette
unit (optional, 20 lb. bond)
10-sheet bypass tray (20 lb. bond)
1-sheet manual feeding for
envelopes, cards,
OHP transparencies

AUTO DOCUMENT FEEDER:
50-sheet capacity

DEVELOPING SYSTEM:
Superfine Micro-Toning
Image Smoothing

HALFTONE REPRODUCTION:
256 grayscale levels

PC CONNECTIVITY:
USB1.1 interface (standard)
Network Interface Card (standard)
Internet Fax/Network Scan
(standard)

MEMORY:
16 MB (standard) (350 fax pages*,
20 copier pages)
48 MB (maximum) (1,024 fax pages*,
170 copier pages)

COPY QUANTITY
99 pages

ZOOM RATIOS:
50% to 200% in 1% increments
Reduction: 78%, 64%, 50%
Enlargement: 129%, 154%, 200%

WARM-UP TIME:
Less than 25 seconds

AUTODIALING LOCATIONS:
264 (200 Speed Dial,
64 One-Touch Dial)

BROADCAST DESTINATIONS:
274 (max)

POLLING LOCATIONS:
30 (max)

POWER SUPPLY:
120 V, 60 Hz

DIMENSIONS (W x H x D):
16-3/4" x 16-1/2" x 27-7/8"

WEIGHT:
31 lbs.

OPTIONS:
500-sheet Second Paper Cassette
Unit (with letter cassette)
32 MB Memory Upgrade

Available Facsimile Functions

Auto Dialing
Speed Dialing: 200 locations
One-Touch Dialing:
64 locations
Auto/Manual Dialing
Batch Transmission
Broadcast (274 destinations)
Confidential Mailbox
Transmission/Reception
(5 mailboxes)
Contrast Control
Closed Network Reception
ECM (Error Correction Mode)
Fax Print and/or Forward
F-Code Support
Group Broadcasting
Memory Backup
Memory Overflow Transmission
Memory Reception/Transmission
Polling Transmission/Reception
Energy Save Mode
Programmable Keys (4)
Reduction Rx
Reports
Sub-addressing
Timer Transmission
Transmission Reservation

GDI Print Driver Specifications

INTERFACE:
USB Revision 1.1
Ethernet 10/100Base-T/TX (RJ-45)

PROTOCOL:
TCP/IP
IPX/SPX

SUPPORTED OPERATING SYSTEMS:
Windows XP (SP1 or later)
Windows 2000 (SP3 or later)
Windows NT Workstation Version
4.0 (SP7a or later)
Windows ME
Windows 98 (SP1)
Windows 98 Second Edition

WEB BROWSER:
Internet Explorer 4.0 or later

TWAIN Driver Specifications

INTERFACE:
USB1.1

SUPPORTED OPERATING SYSTEMS:
Windows XP
Windows 2000
Windows ME
Windows 98 Second Edition



© 2007 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Konica Minolta and The essentials of imaging are trademarks of KONICA MINOLTA HOLDINGS, INC. All other brands and product names are registered trademarks or trademarks of their respective owners

Design & specifications are subject to change without notice.

*Transmit times, page capacity based on ITU-T (CCITT) Test Chart No. 1 (in standard mode)

KONICA MINOLTA FAX
3900



KONICA MINOLTA

KONICA MINOLTA
BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive
Ramsey, NJ 07446
www.kmbs.konicaminolta.us